

K3000

Weighbridge Terminal



Features:

- * SUS304 stainless steel housing, bracket and PG glands
- * IP65 protection
- * 100~240V AC power supply directly
- * Easy to operate with big LCD display
- * User-friendly operation interface
- * Anti-vibration better for oil tank truck, etc.
- * Multi-interface: RS232, RS485, Ethernet, etc.
- * Super anti-interference technology:
 - All communication interface isolated design
 - Anti-surge design
- * K3000 Analog version: drive up to 16*350 Ohm load cells
- * K3000D Digital version: working with Moorage/HBM/AWT/ZEMIC etc.
(all rights of above mentioned brands belong to those companies who registered and owned)
- * High accuracy up to 10,000e
- * Max. display resolution up to 60,000

Specifications:

- * Power: 100~240V, 50/60Hz
- * Excitation voltage: DC10V 500mA, up to 16*350 Ohm load cells
- * A/D rate: 120 times/second
- * Display resolution: 1/3,000~1/60,000
- * Protection: IP65
- * Display: Dot-Matrix LCD 240*128mm
- * Units: kg/t
- * Communication: Continuous/Print/Modbus-RTU/Modbus-TCP
- * Operating temperature: -10°C~40°C
- * Storage temperature: -25°C~55°C
- * Weight: 3.2kg



Atrontec Electronic Tech Co.,Ltd
Web: www.atrontecsales.com
Mob.: 86-13921018341
Email: info@atrontecsales.com

K3000 Industrial Weighing Terminal

Analog and Digital Version, High Accuracy, User-friendly