

## Low-Profile Stainless-Steel Platform



### Features:

- \* Stainless-steel construction, sand-blasting surface, optional anti-skidding design.
- \* Hermetically sealed stainless steel load cell.
- \* Force transfer mechanism can be reset automatically.
- \* The low overall height is 35mm-45mm, allows smooth driving via ramps.
- \* Short ramp with 300mm.

### Accessories:

#### \* Ramp



**Stainless steel**  
(for wet environments)

#### \* Scale stand



**Stainless steel**  
(for fastening the terminal on the weighing platform)

### Specifications:

Model	Dimensions (mm)	Weight Range			
		300kg	600kg	1000kg	1500kg
PCS0808	800x800	*	*	*	*
PCS1010	1000x1000	*	*	*	*
PCS1212	1200x1200	*	*	*	*
PCS1515	1500x1500	*	*	*	*
Verification division value		0.1kg	0.2kg	0.2kg	0.5kg
Accuracy Level		C3			
Working temperature		platform & load cell: -35℃ ~ +65℃			
Relative humidity		≤95% (Need no condensation)			
IP		Load cell IP67			
Load cells		ZEMIC B8D			



Model	L	W	H	L1	W1	H1
PCS0808-0.3	800	800	35	1416	1002	114
PCS0808-0.6	800	800	35	1416	1002	114
PCS0808-1.0	800	800	35	1416	1002	114
PCS1010-0.3	1000	1000	35	1616	1202	114
PCS1010-0.6	1000	1000	35	1616	1202	114
PCS1010-1.0	1000	1000	35	1616	1202	114
PCS1010-1.5	1000	1000	45	1616	1202	114
PCS1212-0.3	1200	1200	45	1816	1402	114
PCS1212-0.6	1200	1200	45	1816	1402	114
PCS1212-1.0	1200	1200	45	1816	1402	114
PCS1212-1.5	1200	1200	45	1816	1402	114
PCS1515-0.6	1500	1500	45	2116	1702	114
PCS1515-1.0	1500	1500	45	2116	1702	114
PCS1515-1.5	1500	1500	45	2116	1702	114

\* Non-standard products can be designed upon customer's requirements, or manufactured as client's drawings.

- All kinds of non-standard platforms & accessories can be customized.

- Different brands load cells are optional. Zemic load cell is installed if no special requirements.