

Square Tube Stainless-Steel Platform



Features:

* Brushed stainless-steel construction and brushed stainless steel load plate (1.4301/AISI 304)

* Hermetically sealed stainless-steel load cell could provide long lasting water proof function.

* Rugged and durable construction makes the platform suitable in heavy duty application.

* Comprehensive product line with various weight ranges and platform sizes

* Multi-functions of load platform combined versatile accessories can meet your exact requirements.

Accessories:

* Scale stand



Stainless steel
(for fastening the terminal on the weighing platform)

* Roller top



Stainless steel
(for wet environments)
Hot galvanized
(For dry environments)


* Ball top



Stainless steel
(for wet environments)
Hot galvanized
(For dry environments)

Specifications:

Model	Dimension s (mm)	Loadcell	Weight Range							
			6kg	15kg	30kg	60kg	150kg	300kg	600kg	
RHS2430	240x300	BE6	*	*						
RHS3040	300x400	BM6E			*	*	*			
RHS4050	400x500	BM6E			*	*	*			
RHS4660	460x600	BM6G			*	*	*	*		
RHS6080S	600x800	BM6G			*	*	*	*	*	
RHS6080H	600x800	BE6			*	*	*	*	*	
RHS3030	300x300	BE6	*	*	*	*	*			
RHS4040	400x400	BM6E			*	*	*			
RHS5050	500x500	BM6E			*	*	*			
RHS6060	600x600	BM6G			*	*	*	*		
RHS8080S	800x800	BM6G			*	*	*	*	*	*
RHS8080H*	800x800	BE6			*	*	*	*	*	*
Verification Division Value			2g	5g	10g	20g	50g	100g	200g	
Accuracy Level: C3										
Working Temperature: -20℃~ +50℃										
Relative Humidity: ≤95% (Need no condensation)										
IP Rating: Load cell IP67, IP68, IP69k										
Load Cell: ZEMIC										



Model	L	W	H	L1	L2	W1	W2	H1	ΦD
RHS2430	300	240	132	310	240	250	180	60	54
RHS3040	400	300	135	410	340	310	240	65	54
RHS4050	500	400	135	510	440	410	340	60	54
RHS4660	600	460	140	610	540	470	400	68	54
RHS6080S	800	600	155	815	740	615	540	84	54
RHS6080H	800	600	185	815	740	615	540	94	54
RHS3030	300	300	132	310	240	310	240	60	54
RHS4040	400	400	135	410	340	410	340	65	54
RHS5050	500	500	135	510	440	510	440	68	54
RHS6060	600	600	160	610	540	610	540	75	54
RHS8080S	800	800	175	820	740	820	740	97	54
RHS8080H	800	800	170	820	740	820	740	97	54

* Non-standard products can be designed upon customer's requirements, or manufactured as client's drawings.

- All kinds of non-standard platforms & accessories can be customized.
- Different brands load cells are optional. Zemic load cell is installed if no special requirements.